



## PACKING INSTRUCTION 352

STATE VARIATION: USG-04

△ OPERATOR VARIATIONS: 5X-01, AA-01, AM-03, AS-02, BW-01, CX-02, FX-02, KA-02, KZ-07, LD-02/06, O3-03, UX-04, X5-04

This instruction applies to flammable liquids with a Class 8 and/or Division 6.1 subsidiary hazard in Packing Group II on passenger aircraft.

The General Packing Requirements of 5.0.2 must be met.

### Compatibility Requirements

- substances must be compatible with their packagings as required by 5.0.2.6;
- metal packagings must be corrosion resistant or with protection against corrosion for substances with a Class 8 subsidiary hazard.

### Closure Requirements

- closures must meet the requirements of 5.0.2.7.

*Single packagings are not permitted.*

### COMBINATION PACKAGINGS

Inner Packaging (see 6.1)	Net quantity per inner packaging	Total net quantity per package
Glass	1.0 L	1.0 L
Metal	1.0 L	
Plastic	1.0 L	

### OUTER PACKAGINGS

Type	Drums						Jerricans			Boxes							
Desc.	Steel	Alu- minium	Ply- wood	Fibre	Plastic	Other metal	Steel	Alu- minium	Plastic	Steel	Alu- minium	Wood	Ply- wood	Recon- stituted wood	Fibre- board	Plastic	Other metal
Spec.	1A1 1A2	1B1 1B2	1D	1G	1H1 1H2	1N1 1N2	3A1 3A2	3B1 3B2	3H1 3H2	4A	4B	4C1 4C2	4D	4F	4G	4H1 4H2	4N

5  
352  
to  
353